

BEST AVAILABLE COPY

KCC 4975 (K-C 19,019)

Amendments to the Claims

The following listing of claims will replace all prior listings, and versions, of the claims in this application.

Listing of Claims

1. (Canceled)
2. (Canceled)
3. (Currently amended) The absorbent article as set forth in claim [[2]] 31, wherein ~~the reduced~~ a ratio of the second spacing frequency of CD strands to the first spacing frequency of MD strands is in a ratio of about 0.9 (CD) to 1.0 (MD).
4. (Original) The absorbent article as set forth in claim 3 wherein the ratio is about 0.75 (CD) to 1.0 (MD).
5. (Original) The absorbent article as set forth in claim 3, wherein the ratio is about 0.5 (CD) to 1.0 (MD).
6. (Original) The absorbent article according to claim 3, wherein the reduced frequency range of CD strands is about 0.9 to 0.5 relative to the frequency of MD strands at 1.0.
7. (Canceled)
8. (Currently amended) The absorbent article as set forth in claim [[7]] 31, wherein the machine direction of the scrim member has end zones and a central zone, and said second ~~reduced~~ spacing frequency spacing of CD strands being provided in said central zone.

KCC 4975 (K-C 19,019)

9. (Canceled)

10. (Currently amended) The absorbent article as set forth in claim [[9]] 32, wherein a strand diameter ratio of the CD strand diameter to the MD strand diameter is less than about 0.95.

11. (Original) The absorbent article as set forth in claim 10, wherein the strand diameter ratio is less than about 0.9.

12. (Original) The absorbent article as set forth in claim 11, wherein the strand diameter ratio is less than about 0.75.

13. (Original) The absorbent article as set forth in claim 12, wherein the strand diameter ratio is less than about 0.5.

14. (Canceled)

15. (Currently amended) The absorbent article as set forth in claim [[1]] 31, wherein at least some of said CD strands are generally elliptical in cross-section and have major and minor axes, the minor axes being arranged substantially normal to a plane of the MD strands.

16. (Currently amended) The absorbent article as set forth in claim [[1]] 15 wherein the MD strands are generally elliptical in cross-section, having major and minor axes, ~~the CD strands are generally elliptical having major and minor axes,~~ the minor axes of the CD strands being on average of a lesser dimension than the minor axes of the MD strands.

17. (Canceled)

KCC 4975 (K-C 19,019)

18. (Currently amended) The absorbent article as set forth in claim [[17]] 34 wherein the CD strands are at least one of notched, abraded ~~es~~ and compressed at predetermined places between preselected MD strands to provide the weakened points.

19. (Original) The absorbent article as set forth in claim 18, wherein the weakened points on one of the CD strands are offset in the cross direction from the weakened points on an adjacent CD strand.

20. (Original) The absorbent article as set forth in claim 18, wherein the weakened points are reduced in at least one transverse dimension of the CD strands as compared to other parts of the CD strands.

21. (Canceled)

22. (Currently amended) The absorbent article as set forth in claim [[17]] 34 wherein the CD strands contain an additive which forms the weakened points.

23. (Original) The absorbent article as set forth in claim 22 wherein the additive is calcium carbonate.

24. - 26. (Canceled)

27. (Currently amended) The absorbent article as set forth in claim [[1]] 31 wherein the absorbent article is a disposable garment.

KCC 4975 (K-C 19,019)

28. (Original) The absorbent article as set forth in claim 27 wherein the absorbent article is a diaper.

29. (Original) The absorbent article as set forth in claim 27 wherein the absorbent article is a child's training pants.

30. (Original) The absorbent article as set forth in claim 27 wherein the absorbent article is one of an adult incontinence diaper, adult incontinence pad, adult incontinence pant and adult incontinence undergarment.

31. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein the MD strands are elongate and are spaced according to a first spacing frequency, and at least some of said CD strands have as a characteristic difference a second spacing frequency different from the first spacing frequency of the MD strands, the second spacing frequency of the CD strands

KCC 4975 (K-C 19,019)

being varied in different zones of the elongate MD strands to provide a variance in stiffness between such zones.

32. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein said MD strands each have a strand diameter, and wherein said CD strands each have as a characteristic difference a strand diameter less than said MD strand diameter.

33. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being

KCC 4975 (K-C 19,019)

interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein both of said MD strands and said CD strands are round in cross-section, the CD strands being smaller in cross-section than the MD strands.

34. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein the network of MD strands and CD strands is formed with at least some of the CD strands being continuous and having weakened points along their lengths to enhance buckling.

KCC 4975 (K-C 19,019)

35. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein the network of MD strands and CD strands is formed with at least some of the CD strands having weakened points along their lengths to enhance buckling, the CD strands being at least one of notched, abraded and compressed at predetermined places between preselected ones of the MD strands to provide the weakened points, and wherein the weakened points on the CD strands are cut through, and such weakened points on one CD strand are offset from the weakened points on an adjacent CD strand.

36. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending

KCC 4975 (K-C 19,019)

in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine direction, wherein the CD strand is corrugated and forms peaks and valleys along the cross direction thereof, said MD strands being arranged to engage the CD strands across the peaks and valleys thereof.

37. (New) An absorbent article for absorbing body fluids comprising an absorbent core constructed and arranged for receiving and holding such fluids and including a reinforcing scrim member intimately associated with the absorbent core to maintain its structural integrity in use, said scrim member comprising a network of machine direction (MD) strands extending in a machine direction, and cross direction (CD) strands extending in a cross direction, at least some of said MD strands and CD strands crossing over each other and being interconnected, said MD strands being selected and formed to provide a predetermined stiffness and strength in supporting said absorbent core in the machine direction, and said CD strands being selected and formed with at least one characteristic difference from said MD strands to provide a stiffness of the absorbent core in the cross direction that is less than said stiffness of the absorbent core in the machine

KCC 4975 (K-C 19,019)

direction, wherein the CD strands are woven under and over the MD strands.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.